




Hexagon Screw DIN 931/DIN EN ISO 4014-M24x90- 8.8, Ma=760Nm,  
Washer DIN 125/DIN EN ISO 7089 -A25, retain with Loctite or similar




please observe the fivefold  
security during welding of  
the Retaining plate



longholedisk

A	B	C	D
F all.	130.000 N	30.000 N	
under static load			



0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95

TYPE OF DOKUMENT: DATA SHEET

WEIGHT [KG]: 51.80

PROJECTION

SAFETY NOTE  
DIN ISO 16016:2007-12

Date

Name

DESIGNATION

SHEET-  
FORMAT

Buhl Maschinenbau e.K.  
Carl-Zeiss-Str. 2  
71065 Sindelfingen

DRAW.

06.03.15

G.Velleuer

SAFETY LOCKING

DINA4

APP.

06.03.15

W.Buhl

ADDITIONAL DESIGNATION

SCALE

GENERAL TOLERANCE  
DIN ISO 2768 m-K

**BUHL**

SA 90H

1:5

FROM	6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2

Buhl Maschinenbau e.K.  
Sindelfingen

DRAWING-NO.:

REV.

01-SA 90 H 02-03

0