




please observe the fivefold security during welding of the Retaining plate

Hexagon Screw DIN 931/DIN EN ISO 4014-M24x90- 8.8, Ma=760Nm, Washer DIN 125/DIN EN ISO 7089 -A25, retain with Loctite or similar



	A	B	C	D
F all.	130.000 N	30.000 N		
under static load				



TYPE OF DOKUMENT: DATA SHEET

SAFETY NOTE
DIN ISO 16016:2007-12

Buhl Maschinenbau e.K.
Carl-Zeiss-Str. 2
71065 Sindelfingen

GENERAL TOLERANCE
DIN ISO 2768 m-K

FROM	6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2

Buhl Maschinenbau e.K.
Sindelfingen

BUHL

	Date	Name
DRAW.	14.08.15	G.Velleuer
APP.	14.08.15	W.Buhl

WEIGHT [KG]: 71.01

PROJECTION

DESIGNATION

SAFETY LOCKING

ADDITIONAL DESIGNATION

SA 90P

DRAWING-NO.:

01-SA 90 P 03-05

SHEET-FORMAT
DINA4

SCALE
1:5

REV.
0