





Socket Head Cap Screw DIN 912/DIN EN ISO 4762 - M16x60 - 8.8, Ma=90Nm,
Washer DIN 125/DIN EN ISO 7089 -A17, retain with Loctite or similar



please observe the fivefold
security during welding of
the Retaining plate



A B C	D
F all. 22.000 N	6.185 N
under static load	



TYPE OF DOKUMENT: DATA SHEET

WEIGHT [KG]: 29.90

PROJEKTION

SAFETY NOTE							
DIN ISO 16016:2007-12							
Buhl Maschinenbau e.K.							
Carl-Zeiss-Str. 2							
71065 Sindelfingen							
GENERAL TOLERANCE							
DIN ISO 2768 m-K							
FROM	6	30	120	400	1000	2000	
TO	6	30	120	400	1000	2000	4000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2	2.0

	Date	Name
DRAW.	24.11.15	G.Velleuer
APP.	26.11.15	W.Buhl
<div><div><div><div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div></div></div><div><div>BUHL</div></div></div>		

DESIGNATION		SHEET-FORMAT	
SAFETY LOCKING		DINA4	
ADDITIONAL DESIGNATION		SCALE	
SA 50EMO T-1S		1:5	
DRAWING-NO.:		REV.	
02-SA 50 EMO T-1S 01-05		0	