



Hexagon Screw DIN 931/DIN EN ISO 4014-M20x90- 8.8, $M_a=320\text{Nm}$,
Washer DIN 125/DIN EN ISO 7089 -A21, retain with Loctite or similar




PNEUMATIC
CONNECTION
G 3/8"



longholedisk

	A B C	D
F all.	60.000 N	17.000 N
under static load		



TYPE OF DOKUMENT: DATA SHEET

WEIGHT [KG]: 48.65 PROJECTION

SAFETY NOTE
DIN ISO 16016:2007-12

Buhl Maschinenbau e.K.
Carl-Zeiss-Str. 2
71065 Sindelfingen

	Date	Name
DRAW.	14.08.15	G.Velleuer
APP.	14.08.15	W.Buhl

DESIGNATION

SAFETY LOCKING

ADDITIONAL DESIGNATION

SA 70P

DRAWING-NO.:

04-SA 70 P 03-05

SHEET-
FORMAT
DINA4

SCALE
1:5

REV.
0

GENERAL TOLERANCE
DIN ISO 2768 m-K

FROM	6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2

Buhl Maschinenbau e.K.
Sindelfingen

BUHL