




Hexagon Screw DIN 931/DIN EN ISO 4014-M12x40- 8.8, Ma=40Nm,
Washer DIN 125/DIN EN ISO 7089 -A13, retain with Loctite or similar



please observe the fivefold security during welding of the Retaining plate




asynchronous
switching




locked



unlocked



	A B C D
F _{all.}	3.000 N
under static load	



Fa.Euchner, safety switch,
NZ2RS-511L060C1631

TYPE OF DOKUMENT: DATA SHEET

SAFETY NOTE

DIN ISO 16016:2007-12

Buhl Maschinenbau e.K.
Carl-Zeiss-Str. 2
71065 Sindelfingen

GENERAL TOLERANCE
DIN ISO 2768 m-K

FROM		6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000	4000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2	2.0

Buhl Maschinenbau e.K.
Sindelfingen

BUHL

WEIGHT [KG]: 11.28

PROJECTION 

DESIGNATION

SAFETY LOCKING

ADDITIONAL DESIGNATION

SA 25EM

DRAWING-NO.:

05-SA 25 EM 01-03

SHEET-
FORMAT
DINA4

SCALE

1:3

REV.