Hexagon Screw DIN 931/DIN EN ISO 4014-M12x40- 8.8, Ma=40Nm,
Washer DIN 125/DIN EN ISO 7089 -A13, retain with Loctite or similar





please observe the fivefold security during welding of the Retaining plate



Fa.Euchner, safety switch, NZ2RS-511SVM5L060 GE





A B C D	
F all.	3.000 N
under static load	



TYPE OF DOKUMENT: DATA SHEET

WEIGHT [KG]: 11.28 PROJECTION

SAFETY NOTE
DIN ISO 16016:2007-12

	Date	Name
DRAW.	19.06.17	G.Velleuer
APP.	19.06.17	W.Buhl

Buhl Maschinenbau e.K.
Carl-Zeiss-Str. 2
71065 Sindelfingen

GENERAL TOLERANCE
DIN ISO 2768 m-K

FROM		6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000	4000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2	2.0

Buhl Maschinenbau e.K. Sindelfingen

BUHL

DESIGNATION
SAFETY LOCKING

ADDITIONAL DESIGNATION
SA 25EM

DRAWING-NO.:
05-SA 25 EM 01-05M12

SHEET-FORMAT
DINA4

SCALE
1:3

REV.
0