



Technical drawing of the U-Schneidwerk (U-cutting tool) showing dimensions and components. The drawing includes the following specifications:



- Overall width: 267
- Hub (stroke): 40
- Maximum depth of cut: max. 30
- Minimum depth of cut: min. 20
- Height of the main body: 80
- Connection: Pneumatischer Anschluss G 1/8 (Pneumatic connection G 1/8)
- Force: F

beim Anschweißen der Halteplatte auf 5-fache Sicherheit achten



	A B C D
F _{zul.}	10.000 N
bei stat. Belastung	



Dokumentenart: Datenblatt												Gewicht [kg]: 23.67				Projektion 							
SCHUTZVERMERK NACH DIN ISO 16016:2007-12 BEACHTEN										Datum		Name		Benennung: Sicherheitsabsteckung				Blatt- format:					
Buhl Maschinenbau e.K. Carl-Zeiss-Str. 2 71065 Sindelfingen								Bearb.		23.06.17		G.Velleuer						DINA4					
								Freig.		23.06.17		W.Buhl		Zusatzbenennung: SA 30PT				Maß- stab:					
Allgemeintoleranz DIN ISO 2768 m-K																		Revision					
von				6		30								120		400						1000	
bis		6		30		120								400		1000		2000		4000		0	
Tol.±		0.1		0.2		0.3								0.5		0.8		1.2		2.0			