




Hexagon Screw DIN 931/DIN EN ISO 4014-M12x40- 8.8, Ma=40Nm,  
Washer DIN 125/DIN EN ISO 7089 -A13, retain with Loctite or similar





please observe the fivefold  
security during welding of  
the Retaining plate



longholedisk

A B C D  
F all. 3.000 N  
under static load



TYPE OF DOKUMENT: DATA SHEET

WEIGHT [KG]: 7.17

PROJECTION

SAFETY NOTE  
DIN ISO 16016:2007-12

Date Name

DESIGNATION

SHEET-FORMAT

Buhl Maschinenbau e.K.  
Carl-Zeiss-Str. 2  
71065 Sindelfingen

DRAW. 14.08.15 G.Velleuer  
APP. 14.08.15 W.Buhl

SAFETY LOCKING  
ADDITIONAL DESIGNATION

DINA4  
SCALE

GENERAL TOLERANCE  
DIN ISO 2768 m-K

BUHL

SA 25P

1:3

FROM	6	30	120	400	1000	2000
TO	6	30	120	400	1000	2000
TOL.±	0.1	0.2	0.3	0.5	0.8	1.2

Buhl Maschinenbau e.K.  
Sindelfingen

DRAWING-NO.:  
15-SA 25 P 02-05

REV.  
0